



# MAMBA

## GRAPHICAL RHAPSODY

### OPTICS

- 13-element 21:1 zoom high-resolution optic system
- Beam aperture: 0.7° to 15°
- Fast motorised linear zoom
- Tempered anti-reflective coated lenses
- 250 mm frontal lens for greater performance

### LIGHT SOURCE

- Luminous flux: 2,600,000 lux at 10 m
- Colour temperature output: 9000 K
- Rated life (L70): up to 12,000 hours
- Speckle-free source

### MOVEMENT

- Highly accurate positioning
- Moving-head operated via either 8- or 16-bit resolution
- High-resolution stepper motors operated via microprocessors to ensure extreme accuracy and smooth movement
- Pan and tilt automatic repositioning
- Moving-head range: infinite pan and tilt rotation

### COLOURS

- Sophisticated colour mixing system providing CMY colour mixing
- Fixed colour wheel with variable CTO, 15 complementary colour filters, 2 minus green filters, 2 multicolour filters and 3 coloured animation sections

### GOBOS

- One indexable rotating gobo wheels with 12 quartz glass gobos, plus open position
- Adjustable-speed rotating gobo in both directions
- Fixed multi-position gobo wheel with instant access to 80 metal gobos
- Gobo diameter: 6.9 mm
- Image diameter: 4.0 mm

### FROST

- 2 frost filters : one light, one heavy

### EFFECTS

- Monochromatic graphical animation effects wheel with continuous rotation in both directions
- 2 set of 4 combinable rotating and indexable prisms
- 2 extra set of 2 combinable rotating and indexable prisms

### DIMMER / STROBE

- Electronic dimmer, allowing perfect light adjustment from 0 to 100% without colour variation
- Strobe effect, with speed adjustment from 1 to 25 flashes per second

### SOFTWARE FEATURES

- Local DMX addressing of luminaire and optional parameters through its built-in LCD control panel
- Remote DMX addressing of luminaire and optional parameters through a standard RDM DMX controller
- Information menu including hour counter, temperature, software version

### HARDWARE FACILITIES

- Graphic LCD display for addressing and special functions settings, with flip function
- 5 menu buttons to set functions
- Excess temperature protection
- Integrated wireless CRMX TiMo RDM receiver from LumenRadio
- IP65 XLR 5 pin male and female connectors for DMX connection
- IP65 RJ45 IN / OUT connectors for ArtNet connection
- IP65 PowerCON TRUE1 TOP male connectors for power connection

### CONTROL

- DMX 512 protocol, through DMX cable or a wireless system
- DMX-RDM compatible
- Stand-alone mode and Main/Follow modes
- ArtNet & sACN protocol through Ethernet cable
- Local control panel, with IP65 LCD display
- Footprint of 47 DMX channels

### POWER SUPPLY

- Electronic supply with active PFC
- 100 to 240 Volts – 50/60Hz
- Power: 800 W maximum

### COOLING SYSTEM

- Advanced liquid cooling system
- Self-adjusting variable speed fans for quiet operation (Auto mode)
- Selectable ventilation user modes with a new Silent Mode
- Safety protection against excess temperature

### HOUSING

- Moving-head skeleton made of aluminium and steel metal plates
- Base in die-cast aluminium
- Heatsinks in aluminium and copper
- Moulded covers in self-extinguishing fire retardant ABS PC (V0 class)
- Two-side handles for transportation
- Four heavy-duty feet for better stability
- IP65 protection rating
- Exterior finish: black (Carbon)

### INSTALLATION

- Fastening bracket system: two Omega ¼ turn brackets designed for use with standard clamps
- Mounting points: four ¼ turn locking fittings allowing installation of Omega brackets on luminaire
- Safety cable attachment point

### OPERATING PARAMETERS

- Operating positions: all (device on floor or fixed to a support)
- Maximum permitted ambient temperature (Ta max): 45° C (113° F)
- Minimum permitted ambient temperature (Ta min): -20° C (-4° F)
- Minimum usage distance: 35 m (114.83 ft).

### COMPLIANCE

- EU (EMC & LVD)
- EMC Directive 2014/30/EU
- LVD Directive 2014/35/EU

### US (Safety & EMC)

- UL 1573
- FCC Part 15, Subpart B: 2018

### SIZE

- Product: 404 x 749 x 366 mm (l x h x d)
- Flight-case foam: 680 x 640 x 500 mm (l x h x d)

### WEIGHT

- Product: 41 kg

### PRODUCT CODES

- 014570: MAMBA - LASER SOURCE IP65 6 SERIES

### LEGAL

- MAMBA is AYRTON registered Trademark
- MAMBA is patent pending

Product shown are for illustration purposes only. Specifications subject to change without notice.

**Confidentiality Notice:** This document is confidential and contains proprietary information and intellectual property of AYRTON. Neither this document nor any of the information contained herein may be reproduced or disclosed under any circumstances without the express written permission of AYRTON. Please be aware that disclosure, copying, distribution or use of this document and the information contained therein is strictly prohibited



**AYRTON**  
Digital Lighting